

- Feature :**
- According to JISC 1609 : 1993 AND CNS 5119 general A class specifications.
  - Spectral response close to CIE luminous spectral efficiency.
  - Measuring intensities of illumination in unit of Lux or Foot-candle.
  - Silicon photo diode and filter. • Cosine angular corrected. • Data Hold.

**TM-201L**



**TM-209**



**TM-209M**



**Specifications :**

TM-201L LED Light Meter	TM-209 LED Light Meter	TM-209M Multi-LED Light Meter
3 1/2 digits LCD with maximum reading 2000	White light LED and all visible light measuring	6 LED light source and whole visible light measuring: L0 → Standard light source A. L1 → LED white day light. L2 → LED RED light. L3 → LED AMBER(Yellow) light. L4 → LED GREEN light. L5 → LED BLUE light. L6 → LED PURPLE light. L7~L9 → Default Standard light source A.
Luminous Intensity Measurement		
99 records storage capacity		
Auto power off with disable function		
Max Hold	Max / Min / AVG hold	
Zero adjustment	Real Zero function	
Manual Ranging	Auto ranging	
Range: 200, 2000, 20000, 200000 LUX 20,200, 2000, 20000 FC	Range: 40, 400, 4,000, 40,000, 400,000 LUX 40, 400, 4,000, 40,000 FC	
Meter Size : 130x55x38mm		
Sensor Size : 80x55x25mm		
Weight : 250g		
±3% (Calibrated to standard incandescent lamp 2856°K and corrected LED day white light) ±8% (other visible light source)	± 3% (Calibrated to standard incandescent lamp 2856°K and corrected LED light source) ± 6% (other visible light source)	