


CODUCTIVITY/TDS METER

Model : YK-22CT

ISO-9001, CE, IEC1010



Lutron



LUTRON ELECTRONIC

The Art of Measurement

CONDUCTIVITY/TDS METER

Model : YK-22CT

FEATURES	
* 2 in 1, professional Conductivity and TDS (Total Dissolved Solids) Meters.	* Conductivity/TDS meter use carbon rod electrode for long life, separte pobe convenient for remote measurement.
* Conductivity meter is included two ranges : 2 mS, 20 mS. TDS meter is with 2 ranges : 2,000 PPM, 20,000 PPM. Temperature measurement range is 0 - 60 °C / 32 - 140 °F	* Microprocessor circuit, intelligent function.
* Conductivity/TDS meter build in automatic temperature compensation circuit, adjustable between 0 to 5.0% per °C.	* Records Maximum and Minimum readings with recall.
	* Data hold.
	* Auto shut off saves battery life.
	* RS 232 PC serial interface.
	* Temperature function with °C & °F display unit.

GENERAL SPECIFICATIONS			
Circuit	Custom one-chip of microprocessor LSI circuit.	Operating Humidity	Max. 80% RH.
Display	51 mm x 32 mm, dual function LCD display 15 mm (0.6") digit size. dual function LCD display,	Power Supply	006P DC 9V battery (Alkaline or Heavy duty type).
Measurement	* Conductivity * TDS (Total Dissolved Soloids) * Temp. (sensing from CD/TDS probe)	Power Current	Approx. DC 6.0 mA. Approx. DC 4.2 mA.
		Weight	210 g/0.46 LB (meter only). 290 g/0.64 LB (meter and probe).
Memory Recall	Records Maximum and Minimum readings with recall.	Dimension	<i>Mian meter :</i> 195 x 68 x 30 mm (7.6 x 2.6 x 1.2 inch).
Data hold	Hold the reading value on the display.		<i>Conductivity/TDS probe :</i> Round, 22 mm Dia. x 120 mm length.
Power off	Auto shut off saves battery life, or manual off by push button.	Accessories included	Conductivity/TDS probe, YK-200PCT... 1 PC. Operation manual..... 1 PC. Carrying case, CA-06..... 1 PC.
Data Output	RS 232 computer serial interface.	Optional Accessories	1.413 mS Conductivity Standard Solution..... CD-14
Overload indication	"- - - -" symbol on the display.		RS232 cable,..... UPCB-02
Operating Temperature	0 to 50 °C - main instrument. 0 to 60 °C - Conductivity/CT probe only.		USB cable,..... USB-01
Sampling Time	Approx. 0.8 second.		Application Software..... SW-U801-WIN

ELECTRICAL SPECIFICATIONS (23 ± 5 °C)			
* Conductivity/TDS meter specifications			
<i>Measurement</i>	<i>Range</i>	<i>Resolution</i>	<i>Accuracy</i>
Conductivity	2 mS (0 to 2,000 mS)	0.001 mS	± (3 % F.S. + 1 d) * F.S. - Full scale
	20 mS (2 to 20.00 mS)	0.01 mS	
TDS	2,000 PPM (0 to 1,320 PPM)	1 PPM	* mS - milli Simens * PPM - parts per million
	20,000 PPM (1,320 to 13,200 PPM)	10 PPM	
Temperature	0 °C to 60 °C	0.1 °C	± 0.8 °C
	32 °F to 140 °F	0.1 °F	± 0.8 °C
* Temperature Compensation : Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per C.			
* mS - milli Simens			
* mS - milli Simens			
* PPM - parts per million			

APPLICATIONS			
* AQUARIUMS	* FOOD PROCESSING	* PAPER INDUSTRY	* SCHOOLS & COLLEGES
* BEVERAGE	* PHOTOGRAPHY	* PLATING INDUSTRY	* SWIMMING POOLS
* FISH HATCHERIES	* LABORATORY	* QUALITY CONTROL	* WATER CONDITIONING

* Appearance and specifications listed in this brochure are subject to change without notice.

1008-YK22CT